



# TECHNICAL DATA

## GB 2T SUPER

### APPLICATIONS

GB 2T SUPER is a semi-synthetic self-mix two-stroke oil, formulated using the latest additive technology for use in a wide range of applications, such as motor cycles, scooters, chainsaws, strimmers, trimmers, blowers, snowmobiles and most other types of air-cooled two-stroke engines.

### PERFORMANCE FEATURES

GB 2T SUPER utilises low-ash, clean-burning technology and offers the following features:

- Reduced spark-plug fouling
- Reduced pre-ignition
- Reduced ring-sticking
- Reduced smoke
- Effective protection against corrosion
- Effective protection against wear
- Clean burning characteristics
- Dye for easy visibility when mixed with fuel

### DILUTION

GB 2T SUPER has a treatment of 2% and above, dependent upon the manufacturer's recommendations. The oil should be added to the petrol. Do not add petrol to the oil. GB 2T SUPER can also be used via a direct injection system.

Cont'd.../...

## **GB LUBRICANTS**

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312

Fax: 0191 477 9544

e-mail: [gblsales@gb lubricants.co.uk](mailto:gblsales@gb lubricants.co.uk)

[www.gb lubricants.co.uk](http://www.gb lubricants.co.uk)

A division of Goodall Bates & Todd Ltd



Integrated Management System  
PAS 99 IMR 560337  
ISO 9001  
ISO 14001  
OHSAS 18001

# GB LUBRICANTS

**PERFORMANCE DETAILS**

GB 2T SUPER may be used where the following specifications are required:

API TC	JASO FD (quality level)
ISO-L-EGD	TISI (quality level)

**CHARACTERISTICS**

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
Appearance	-	-	Red Liquid
Density @ 15°C	kg/m <sup>3</sup>	ASTM D4052	871
Kinematic Viscosity @ 40°C	cSt	ASTM D445	49.6
Kinematic Viscosity @ 100°C	cSt	ASTM D445	8.1
Viscosity Index	-	ASTM D2270	135
Flash Point (PMCC)	°C	ASTM D93	94
Pour Point	°C	ASTM D97	-21

**STORAGE AND HANDLING**

GB 2T SUPER should be stored under cover to avoid water collecting in the rim of upturned barrels.

**HEALTH, SAFETY AND THE ENVIRONMENT**

Further information on GB 2T SUPER can be obtained by referring to the corresponding Safety Data Sheet.

For guidance on storage and handling of all lubricants and related products, GB Lubricants recommend the Environment Agency, [www.environment-agency.gov.uk](http://www.environment-agency.gov.uk), as an excellent source of advice.

If you have any queries, please do not hesitate to contact either your local Technical Sales Representative or our Technical Department.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations and specifications, without prior notice.