



TECHNICAL DATA

GB CHAINSAW OILS

APPLICATIONS

GB CHAINSAW OILS are specially developed dedicated chain oils with adhesive properties, which will protect and lubricate the chains and bars of chainsaws. Used correctly, they will prolong the life of the chain and reduce breakage.

PERFORMANCE FEATURES

GB CHAINSAW OILS are formulated using the highest quality mineral virgin base oils and selected additives to offer the following features:

- Suitability for use on petrol or electrical powered chainsaws
- Excellent anti-fling
- Good antiwear protection
- Good corrosion protection
- Extended working life

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS		
			80	150	220
Density @15°C	kg/m ³	IP 160	874	893	897
Kinematic Viscosity @40°C	cSt	IP 71	83.0	147.3	218.7
Kinematic Viscosity @100°C	cSt	IP 71	10.1	15.0	19.4
Viscosity Index	-	IP 226	102	102	100
Pour Point	°C	IP 15	-18	-15	-15

Cont'd.../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP


Tel: 0191 490 4312

Fax: 0191 477 9544

e-mail: gblsales@gb lubricants.co.uk

www.gblubricants.co.uk

A division of Goodall Bates & Todd Ltd



STORAGE AND HANDLING

GB CHAINSAW OILS should be stored under cover to avoid water collecting in the rim of upturned barrels.

Further information on GB CHAINSAW OILS can be obtained by referring to the corresponding Safety Data Sheet.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice.