

<u>GB GERION[®] EP 80W-90</u>

APPLICATIONS

GB GERION[®] EP 80W-90 has been developed using the highest quality virgin mineral base oils and advanced additive systems, for use in transmissions and gears requiring an API GL-4 level of performance. It may also be used in final drives and axles, when specified by Original Equipment Manufacturers.

PERFORMANCE FEATURES

GB GERION[®] EP 80W-90 is formulated to satisfy the higher performance demands of today's drivetrain lubricants and offers the following features:

- Enhanced gear changes
- Thermal stability
- Oxidation stability
- Anti-wear performance
- Corrosion protection
- Load-carrying properties
- Low foaming

PERFORMANCE DETAILS

GB GERION[®] EP 80W-90 may be used where the following specification is required:

API GL-4

Cont'd .../...



Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312 Fax: 0191 477 9544 e-mail: gblsales@gb-lubricants-fuels.co.uk www.gb-lubricants-fuels.co.uk

A division of Goodall Bates & Todd Ltd



GB LUBRICANTS

GB GERION[®] EP 80W-90

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
SAE			80W-90
Density @ 15°C	kg/m ³	IP 160	891
Kinematic Viscosity @ 40°C	cSt	IP 71	154.7
Kinematic Viscosity @ 100°C	cSt	IP 71	15.7
Viscosity Index	-	IP 226	105
Brookfield Viscosity @ -26°C	cP	ASTM D 2983	150,000
Flash Point	°C	IP 34	188
Pour Point	°C	IP 15	-30

CHARACTERISTICS

STORAGE AND HANDLING

GB GERION[®] EP 80W-90 should be stored under cover to avoid water collecting in the rim of upturned barrels.

HEALTH, SAFETY AND THE ENVIRONMENT

Further information on GB GERION[®] EP 80W-90 can be obtained by referring to the corresponding Material Safety Data Sheet.

For guidance on storage and handling of all lubricants and related products, GB Lubricants recommend the Environment Agency, <u>www.environment-agency.gov.uk</u>, as an excellent source of advice.

If you have any queries, please do not hesitate to contact either your local Technical Sales Representative or our Technical Department.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations and specifications, without prior notice.

TDS44.0513.09