



# TECHNICAL DATA

## **GB FLUSHING OIL (STRAIGHT)**

A flushing oil for use in engines

### **APPLICATIONS**

GB FLUSHING OIL (STRAIGHT) has been formulated using the highest quality mineral virgin base oils to provide a flushing oil with a wide variety of applications.

### **DIRECTIONS FOR USE**

- The oil, whilst warm, should be drained in the normal way and the sump drain plug replaced.
- GB FLUSHING OIL (STRAIGHT) should then be added to the normal sump capacity.
- Start the engine and idle at low revolutions for 15 minutes with occasional bursts at higher revolutions.
- Stop the engine, drain in the normal way and replace the sump drain plug. If it appears very dirty, it is advisable to repeat the process with new GB FLUSHING OIL (STRAIGHT).
- Renew the oil filter or clean external oil filter, whichever is applicable.
- Refill with the correct grade of GB Lubricants engine oil.

NB: The vehicle should not be driven on the road containing only GB FLUSHING OIL (STRAIGHT) as the lubricant.

GB FLUSHING OIL (STRAIGHT) should not be used on Leyland engines with automatic gearboxes contained in the sump, or automatic transmissions.

### **CHARACTERISTICS**

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
Density @ 15°C	kg/m <sup>3</sup>	IP 160	875
Kinematic Viscosity @ 40°C	cSt	IP 71	32.5
Kinematic Viscosity @ 100°C	cSt	IP 71	5.38
Viscosity Index		IP 226	98
Pour Point	°C	IP 15	-12

## **GB LUBRICANTS**

Cont'd.../...

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312  
Fax: 0191 477 9544  
e-mail: gblsales@gb lubricants.co.uk  
www.gb lubricants.co.uk

Trading Name of Goodall Bates & Todd Ltd



## GB FLUSHING OIL (STRAIGHT)

### **STORAGE AND HANDLING**

GB FLUSHING OIL (STRAIGHT) should be stored under cover to avoid water collecting in the rim of upturned barrels.

Further information on GB FLUSHING OIL (STRAIGHT) can be obtained by referring to the corresponding Safety Data Sheet.

***The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice.***

TDS193.0525.03