



TECHNICAL DATA

GB KT MOULD OIL

APPLICATIONS

GB KT MOULD OIL has been formulated using the highest quality mineral virgin base oils and a specially selected reactive additive, to form a release layer between the setting concrete and the mould. It is particularly suited for fast moving production industries, where time constraints apply.

PERFORMANCE FEATURES

GB KT MOULD OIL offers the following features:

- Suitable for use on a wide range of mould materials
- Ideal for use on large surface areas
- Provides a superior surface finish
- Provides a clean release
- Good wetting-out properties

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
Appearance	-	-	Pale yellow liquid
Density @ 15°C	kg/m ³	ASTM D4052	834
Kinematic Viscosity @ 40°C	cSt	ASTM D445	5.0
Flash Point (PMCC)	°C	ASTM D93	54

Cont'd.../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312
Fax: 0191 477 9544
e-mail: gblsales@gb lubricants.co.uk
www.gblubricants.co.uk

Trading Name of Goodall Bates & Todd Ltd



STORAGE AND HANDLING

GB KT MOULD OIL should be stored under cover to avoid water collecting in the rim of upturned barrels.

Further information on GB KT MOULD OIL can be obtained by referring to the corresponding Safety Data Sheet.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice.