



TECHNICAL DATA

GB CALIBRATION FLUID 4113

A calibration and storage oil for diesel fuel injectors

APPLICATIONS

GB CALIBRATION FLUID 4113 has been specially developed for use as a calibration and storage oil for diesel fuel injectors.

PERFORMANCE FEATURES

GB CALIBRATION FLUID 4113 is formulated with rust preventative properties, so that without cleaning the equipment after calibration, proper functioning is maintained for up to one year's storage.

PERFORMANCE DETAILS

GB CALIBRATION FLUID 4113 may be used where the following specifications are required:

ISO 4113

LUCAS CAV 7-10-106

CHARACTERISTICS

TEST	UNIT	TYPICAL PHYSICAL CHARACTERISTICS
Density @ 15°C	Kg/m ³	825
Kinematic Viscosity @ 40°C	cSt	2.45 – 2.60
Flash Point (Open)	°C	110
Rust Prevention (ASTM D1748:50 hours)		Pass for five out of six faces on three panels

Cont'd.../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312

Fax: 0191 477 9544

e-mail: gblsales@gblubricants.co.uk

www.gblubricants.co.uk

Trading Name of Goodall Bates & Todd Ltd



GB LUBRICANTS

GB CALIBRATION FLUID 4113

STORAGE AND HANDLING

GB CALIBRATION FLUID 4113 should be stored under cover to avoid water collecting in the rim of upturned barrels.

Further information on GB CALIBRATION FLUID 4113 can be obtained by referring to the corresponding Safety Data Sheet.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice.

TDS173.0525.04