



TECHNICAL DATA

GB SOLVENT CLEANER

An emulsifiable diphasic solvent degreaser

APPLICATIONS

GB SOLVENT CLEANER has been developed using hydrocarbon solvents and emulsifiers to quickly penetrate dirty oily deposits on the surfaces of machinery, vehicles, floors, paintwork etc, which can then be flushed clean with cold water.

PERFORMANCE FEATURES

GB SOLVENT CLEANER is formulated to offer the following features:

- Application by spraying, dipping, soaking or brushing
- It wets the surface with a continuous film of solvent
- The ability to wet, penetrate and solubilise dirty oily deposits
- Cost effectiveness

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
Appearance	-	-	Pale Yellow liquid
Density @ 15°C	kg/m ³	ASTM D4052	803
Kinematic Viscosity @ 40°C	cSt	ASTM D445	1.7
Flash Point (PMCC)	°C	ASTM D93	80

Cont'd.../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312
Fax: 0191 477 9544
e-mail: gblsales@gb lubricants.co.uk
www.gblubricants.co.uk

Trading Name of Goodall Bates & Todd Ltd



GB SOLVENT CLEANER

STORAGE AND HANDLING

GB SOLVENT CLEANER should be stored under cover to avoid water collecting in the rim of upturned barrels.

Further information on GB SOLVENT CLEANER can be obtained by referring to the corresponding Safety Data Sheet.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice.

TDS103.0525.09