



TECHNICAL DATA

GB GRAPHITED PENETRATING OIL

APPLICATIONS

GB GRAPHITED PENETRATING OIL has been developed using the highest quality mineral virgin base oils and selected additives for use as a penetrating fluid.

PERFORMANCE FEATURES

GB GRAPHITED PENETRATING OIL offers the following features:

- Release of rust-bound components
- Dust-removal and protection
- Maintenance of properties in damp conditions
- The use of graphite to aid release of stubborn nuts and bolts

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
Appearance	-	-	Dark Grey/Black
Density @ 15°C	kg/m ³	ASTM D4052	832
Kinematic Viscosity @ 40°C	cSt	ASTM D445	4.0
Flash Point (PMCC)	°C	ASTM D93	52

Cont'd.../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312
Fax: 0191 477 9544
e-mail: gblsales@gb lubricants.co.uk
www.gblubricants.co.uk

Trading Name of Goodall Bates & Todd Ltd



GB GRAPHITED PENETRATING OIL

STORAGE AND HANDLING

GB GRAPHITED PENETRATING OIL should be stored under cover to avoid water collecting in the rim of upturned barrels.

Further information on GB GRAPHITED PENETRATING OIL can be obtained by referring to the corresponding Safety Data Sheet.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice.

TDS 224.0525.04