



TECHNICAL DATA

GB PENETRATING OIL

APPLICATIONS

GB PENETRATING OIL has been developed using the highest quality mineral virgin base oils and selected additives for use as a penetrating fluid.

PERFORMANCE FEATURES

GB PENETRATING OIL offers the following features:

- Release of rust-bound components
- Dust-removal and protection
- Maintenance of properties in damp conditions
- A non-staining product

CHARACTERISTICS

| TEST | UNIT | METHOD | TYPICAL PHYSICAL CHARACTERISTICS |
|----------------------------|-------------------|------------|----------------------------------|
| Appearance | | | Pale Yellow Liquid |
| Density @ 15°C | kg/m ³ | ASTM D4052 | 828 |
| Kinematic Viscosity @ 40°C | cSt | ASTM D445 | 4.0 |
| Flash Point (PMCC) | °C | ASTM D93 | 52 |

STORAGE AND HANDLING

GB PENETRATING OIL should be stored under cover to avoid water collecting in the rim of upturned barrels.

Cont'd.../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312
Fax: 0191 477 9544
e-mail: gblsales@gb lubricants.co.uk
www.gblubricants.co.uk

Trading Name of Goodall Bates & Todd Ltd



GB LUBRICANTS

GB PENETRATING OIL

Further information on GB PENETRATING OIL can be obtained by referring to the corresponding Safety Data Sheet.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice.

TDS196.0525.04