



TECHNICAL DATA

GB HONING FLUID

APPLICATIONS

GB HONING FLUID has been formulated using the highest quality mineral virgin base oils, combined with inactive sulphur and chlorinated extreme pressure additives. Developed for general purpose automotive machine shop honing, it is excellent for con rods, piston pins, king pins and can also be used as a screw machine and general purpose cutting oil.

ADVANTAGES

GB HONING FLUID offers the following features:

- Non-staining towards yellow metals
- Pale colour
- Low odour
- Good fines separation
- Good filterability

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
Appearance	-	-	Light amber liquid
Density @ 15°C	kg/m ³	IP 160	880
Kinematic Viscosity @ 40°C	cSt	IP 71	16.0
Flash Point	°C	IP 34	155

Cont'd.../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312
Fax: 0191 477 9544
e-mail: gblsales@gblubricants.co.uk
www.gblubricants.co.uk

Trading Name of Goodall Bates & Todd Ltd



GB LUBRICANTS

STORAGE AND HANDLING

GB HONING FLUID should be stored under cover to avoid water collecting in the rim of upturned barrels.

Further information on GB HONING FLUID can be obtained by referring to the corresponding Safety Data Sheet.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice.

TDS145.0525.05