



TECHNICAL DATA

GB UNICUT® 7

A medium viscosity cutting oil, incorporating an inactive sulphurised extreme pressure additive.

APPLICATIONS

GB UNICUT® 7 is a medium viscosity cutting oil containing lubricity additive, together with a very low corrosivity extreme pressure sulphurised ester. The cutting oil is classified as inactive and can be used for operations on cuprous and aluminium alloys and for a wide variety of general purpose cutting.

PERFORMANCE FEATURES

Special features of GB UNICUT® 7 are:

- Its high quality mineral virgin basestock
- Its medium viscosity
- Its high lubricity level
- The use of an inactive sulphurised fatty ester
- Its possible use as a combined general purpose cutting oil AND slideway lubricating oil

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
Appearance			Amber fluid
Kinematic Viscosity @ 40°C	cSt	IP 71	33.9
Density @15°C	kg/m ³	IP 160	878
Flash Point	°C	IP 34	200

Cont'd.../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312
Fax: 0191 477 9544
e-mail: gblsales@gb lubricants.co.uk
www.gblubricants.co.uk

Trading Name of Goodall Bates & Todd Ltd



STORAGE AND HANDLING

GB UNICUT® 7 should be stored under cover to avoid water collecting in the rim of upturned barrels.

Further information on GB UNICUT® 7 can be obtained by referring to the corresponding Safety Data Sheet.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice.