



TECHNICAL DATA

GB UNICUT® 9

APPLICATIONS

GB UNICUT® 9 is formulated for operations which are sensitive to staining, such as broaching alloy steels, machining heat-resistant steels and nickel alloys and tube-drawing cuprous and stainless steels. This chlorinated EP product can also be used as a tapping fluid.

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
Appearance			Yellow liquid
Kinematic Viscosity @ 40°C	cSt	IP 71	35
Density @ 15°C	kg/m ³	IP 160	1130
Flash Point	°C	IP 34	>150

STORAGE AND HANDLING

GB UNICUT® 9 should be stored under cover to avoid water collecting in the rim of upturned barrels.

Further information on GB UNICUT® 9 can be obtained by referring to the corresponding Safety Data Sheet.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice.

TDS136.1117.08

GB LUBRICANTS

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312

Fax: 0191 477 9544

e-mail: gblsales@gb lubricants.co.uk

www.gb lubricants.co.uk

A division of Goodall Bates & Todd Ltd



Integrated Management System
PAS 99 IMR 560337
ISO 9001
ISO 14001
OHSAS 18001