



TECHNICAL DATA

GB TURBO X 15W-50

APPLICATIONS

GB TURBO X 15W-50 is formulated using the highest quality virgin mineral base oils and enhanced additive systems for use in both petrol and diesel passenger car engines. These include high-performance, turbo-charged passenger cars as well as naturally aspirated models; it may also be used in light trucks and vans.

PERFORMANCE FEATURES

GB TURBO X 15W-50 has been developed for high performance passenger cars and offers the following features:

- Improved engine wear protection
- Rust and corrosion protection
- Excellent piston deposit control
- Excellent oxidation stability

PERFORMANCE DETAILS

GB TURBO X 15W-50 may be used where the following specifications are referenced:

| | |
|------------|----------------------|
| ACEA A3/B4 | MERCEDES BENZ p229.1 |
| API SN/CF | VW 501 01/505 00 |

Cont'd.../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312

Fax: 0191 477 9544

e-mail: gblsales@gblubricants.co.uk

www.gblubricants.co.uk

A division of Goodall Bates & Todd Ltd



Integrated Management System
PAS 99 IMR 560337
ISO 9001
ISO 14001
OHSAS 18001

GB LUBRICANTS

CHARACTERISTICS

| TEST | UNIT | METHOD | TYPICAL PHYSICAL CHARACTERISTICS |
|-----------------------------|-------------------|------------|----------------------------------|
| SAE | | | 15W-50 |
| Appearance | - | - | Clear amber liquid |
| Kinematic Viscosity @ 100°C | cSt | ASTM D445 | 17.8 |
| Kinematic Viscosity @ 40°C | cSt | ASTM D445 | 137.4 |
| Viscosity Index | - | ASTM D2270 | 144 |
| Density | kg/m ³ | ASTM D1298 | 878 |
| CCS @ -20°C | cP | ASTM D5293 | 5825 |
| HTHS @ 150°C | mPa.s | ASTM D4683 | 4.3 |
| Noack | % | ASTM D5800 | 8.3 |
| Sulphated Ash | % mass | ASTM D874 | 1.1 |

STORAGE AND HANDLING

GB TURBO X 15W-50 should be stored under cover to avoid water collecting in the rim of upturned barrels.

Further information on GB TURBO X 15W-50 can be obtained by referring to the corresponding Safety Data Sheet.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice.