



TECHNICAL DATA

GB UNIGEAR® SHC RANGE

APPLICATIONS

The GB UNIGEAR® SHC RANGE has been developed as a premium range of synthetic gear and bearing oils. It is formulated on polyalpha-olefin base fluids and specially selected extreme pressure additives, to give excellent performance in precision gear boxes and heavily loaded or shock-loaded gears and bearings, at both high and low temperatures.

PERFORMANCE FEATURES

The GB UNIGEAR® SHC RANGE of synthetic industrial gear oils offers the following features:

- Proven field performance in wind turbine applications
- Consistently strong micro-pitting performance
- Clean gear performance under conditions of high temperature and oxidation
- Outstanding bearing and tooth wear protection
- Extended corrosion and foam performance
- Good compatibility with mineral lubricants and related paints, seals etc.
- Improved efficiency and long service life
- Excellent phosphorous retention, ensuring extended wear protection
- Low chlorine content
- Wide operating temperature range from -40°C to +180° C

PERFORMANCE DETAILS

The GB UNIGEAR® SHC RANGE may be used where the following specifications are required:

US STEEL 224	Flender AG approved FZG micro-pitting performance (ISOs 220-680)
AGMA 9005-E02	DAVID BROWN S1.53.101
DIN 51517 part 3	CINCINNATI MACHINE P-74

Cont'd.../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312

Fax: 0191 477 9544

e-mail: gblsales@gblubricants.co.uk

www.gblubricants.co.uk

A division of Goodall Bates & Todd Ltd



Integrated Management System
PAS 99 IMR 560337
ISO 9001
ISO 14001
OHSAS 18001

GB LUBRICANTS

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS		
ISO			68	150	220
Appearance	-	Visual	Pale amber liquid	Pale amber liquid	Pale amber liquid
Density @ 15°C	kg/m ³	IP 160	855	861	864
Kinematic Viscosity @ 40°C	cSt	IP 71	69.2	155.6	215.7
Kinematic Viscosity @ 100°C	cSt	IP 71	10.9	20.0	26.1
Viscosity Index	-	IP 226	148	149	154
Flash Point	°C	IP 34	193	193	187
FZG (A/16.6/90)	-	DIN 51354 part 2	>12	>12	>12

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS		
ISO			320	460	680
Appearance	-	Visual	Pale amber liquid	Pale amber liquid	Pale amber liquid
Density @ 15°C	kg/m ³	IP 160	866	867	868
Kinematic Viscosity @ 40°C	cSt	IP 71	330.3	483.1	732.1
Kinematic Viscosity @ 100°C	cSt	IP 71	36.0	49.1	68.1
Viscosity Index	-	IP 226	155	161	166
Flash Point	°C	IP 34	188	188	191
FZG (A/16.6/90)	-	DIN 51354 part 2	>12	>12	>12

STORAGE AND HANDLING

The GB UNIGEAR® SHC RANGE should be stored under cover to avoid water collecting in the rim of upturned barrels.

Further information on The GB UNIGEAR® SHC RANGE can be obtained by referring to the corresponding Safety Data Sheet.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice.