



TECHNICAL DATA

GB UNITRANS® C 80W-140

APPLICATIONS

GB UNITRANS® C 80W-140 has been formulated using the highest quality mineral virgin base oils and multifunctional additives, specifically as a drive train lubricant for certain Case Loader/Backhoe model transaxles and axles with oil-immersed brake systems.

PERFORMANCE FEATURES

GB UNITRANS® C 80W-140 transaxle fluid offers the following features:

- Excellent gear wear protection
- Good brake chatter control
- Improved oxidation stability
- Increased gear loading
- Excellent low temperature performance

PERFORMANCE DETAILS

GB UNITRANS® C 80W-140 may be used where the following specification is required:

CASE MS1317 (CNH MAT 3510)

Cont'd.../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312

Fax: 0191 477 9544

e-mail: gblsales@gb-lubricants-fuels.co.uk

www.gb-lubricants-fuels.co.uk

A division of Goodall Bates & Todd Ltd



Integrated Management System
PAS 99 IMR 560337
ISO 9001
ISO 14001
OHSAS 18001

GB LUBRICANTS

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
SAE			80W-140
Appearance	-	-	Amber liquid
Density @ 15°C	kg/m ³	IP 160	903
Kinematic Viscosity @ 40°C	cSt	IP 71	231
Kinematic Viscosity @ 100°C	cSt	IP 71	29.5
Viscosity Index	-	IP 226	167
Brookfield Viscosity @ -26°C	cP	ASTM D2983	97,000

STORAGE AND HANDLING

GB UNITRANS® C 80W-140 should be stored under cover to avoid water collecting in the rim of upturned barrels.

HEALTH, SAFETY AND THE ENVIRONMENT

Further information on GB UNITRANS® C 80W-140 can be obtained by referring to the corresponding Material Safety Data Sheet.

For guidance on storage and handling of all lubricants and related products, GB Lubricants recommend the Environment Agency, www.environment-agency.gov.uk, as an excellent source of advice.

If you have any queries, please do not hesitate to contact either your local Technical Sales Representative or our Technical Department.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations and specifications, without prior notice