



# TECHNICAL DATA

## GB UNITRANS® WB2

### APPLICATIONS

GB UNITRANS® WB2 is a high performance, synthetic based universal tractor transmission oil (UTTO) for use in agricultural, plant and other off-highway applications. GB UNITRANS® WB2 may be used in powershift transmissions, hydrostatic drives, transaxle/hydraulic systems, wet brakes, PTO boxes, final drives, torque converters, reduction hubs and power steering systems.

### PERFORMANCE FEATURES

GB UNITRANS® WB2 is formulated to provide superior gear performance, squawk and chatter suppression, hydraulic pump protection and low temperature performance in modern off-highway equipment and offers the following features:

- Superior gear and pump wear protection
- Precise clutch and wet brake operation
- Oxidation and thermal stability
- Exceptional corrosion protection
- Low foam

### PERFORMANCE DETAILS

GB UNITRANS® WB2 meets the performance requirements of many Original Equipment Manufacturers, and may be used where the following specifications are required:

API GL-4	JOHN DEERE J20C
ALLISON C-4	MASSEY FERGUSON M1135/M1143
CNH MAT 3525	ZF TE-ML-03E/05F/06K
CATERPILLAR TO-2	VOLVO WB102*
FORD M2C86-B	*meets the performance requirements of this Volvo Transmission Oil 97304 specification
FORD M2C134-D	

Cont'd.../...

## **GB LUBRICANTS**

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312

Fax: 0191 477 9544

e-mail: [gblsales@gblubricants.co.uk](mailto:gblsales@gblubricants.co.uk)

[www.gblubricants.co.uk](http://www.gblubricants.co.uk)

A division of Goodall Bates & Todd Ltd



Integrated Management System  
PAS 99 IMR 560337  
ISO 9001  
ISO 14001  
OHSAS 18001

# GB LUBRICANTS

**CHARACTERISTICS**

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
Appearance	-	-	Clear amber liquid
Density @ 15°C	kg/m <sup>3</sup>	ASTM D4052	860
Kinematic Viscosity @ 40°C	cSt	ASTM D445	39.7
Kinematic Viscosity @ 100°C	cSt	ASTM D445	7.6
Viscosity Index	-	ASTM D2270	165
Flash Point (PMCC)	°C	ASTM D93	200
Pour Point	°C	ASTM D97	-45

**STORAGE AND HANDLING**

GB UNITRANS® WB2 should be stored under cover to avoid water collecting in the rim of upturned barrels.

Further information on GB UNITRANS® WB2 can be obtained by referring to the corresponding Safety Data Sheet.

***The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice.***