



TECHNICAL DATA

GB TR1

GB TR1 is a specially formulated asphalt release agent for the construction industry. This readily biodegradable product is an environmentally acceptable alternative to using diesel when preventing build-up of tar and bitumen in tipper beds, chutes and tailgates.

METHOD OF APPLICATION

GB TR1 can be applied by a hand held sprayer, or brushed on to, the surfaces that come into contact with bitumen.

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
Appearance	-	-	Pale yellow liquid
Density @ 20°C	kg/m ³	ASTM D4052	880
Kinematic Viscosity @ 40°C	cSt	ASTM D445	5.0
Flash point, COC	°C	ASTM D92	185
Pour Point	°C	ASTM D97	-12

STORAGE AND HANDLING

GB TR1 should be stored under cover and protected from freezing temperatures.

Further information on GB TR1 can be obtained by referring to the corresponding Safety Data Sheet.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice.

TDS331.0320.01

GB LUBRICANTS

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312

Fax: 0191 477 9544

e-mail: gblsales@gb lubricants.co.uk

www.gblubricants.co.uk

A division of Goodall Bates & Todd Ltd



GB LUBRICANTS

