



# TECHNICAL DATA

## GB SEWING MACHINE OIL

### APPLICATIONS

GB SEWING MACHINE OIL is based on a highly refined, high purity paraffinic white oil and is water white in appearance. Specially developed for use in the textile and clothing industry.

### CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
Appearance	-	-	Water white
Density @ 15°C	kg/m <sup>3</sup>	ASTM D1298	865
Kinematic Viscosity @ 40°C	cSt	ASTM D445	15
Flash Point	°C	ASTM D92	180

### STORAGE AND HANDLING

GB SEWING MACHINE OIL should be stored under cover to avoid water collecting in the rim of upturned barrels.

Further information on GB SEWING MACHINE OIL can be obtained by referring to the corresponding Safety Data Sheet.

***The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice.***

TDS164.1020.03

## **GB LUBRICANTS**

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312

Fax: 0191 477 9544

e-mail: [gblsales@gblubricants.co.uk](mailto:gblsales@gblubricants.co.uk)

[www.gblubricants.co.uk](http://www.gblubricants.co.uk)

A division of Goodall Bates & Todd Ltd



