



TECHNICAL DATA

GB GERION® EXTRA 75W-80

APPLICATIONS

GB GERION® EXTRA 75W-80 is a synthetic technology, heavy-duty manual transmission oil, formulated using the highest quality base fluids, combined with advanced additive systems, for use in commercial vehicle manual synchromesh transmissions. Suitable for ZF service fill applications and the Volvo I-Shift service recommendation, GB GERION® EXTRA 75W-80 has been designed to withstand the severe conditions imposed by commercial vehicle operations and provides total reliability at all times, whilst providing improved fuel economy.

PERFORMANCE FEATURES

GB GERION® EXTRA 75W-80 is formulated as a premium commercial vehicle manual transmission fluid and offers the following features:

- Enhanced gear changes
- Excellent low temperature fluidity
- Thermal and oxidative stability
- Anti-wear performance
- Corrosion protection
- Extreme pressure performance
- Improved frictional properties
- Seal compatibility
- Enhanced synchromesh performance
- Extended drain intervals
- Fuel economy improvement

PERFORMANCE DETAILS

GB GERION® EXTRA 75W-80 may be used where the following specifications are required:

API GL-4	MAN 341 Z-4
DAF	RENAULT (in accordance with Renault Note Technique B0032/2 annex 3)
Eaton Extended Drain	VOLVO 97305
IVECO	ZF TE-ML 01L, 02L, 08, 13, 16K, 24A

Fulfils the technical requirements of Volvo Standard 1273,07 [97307]

Cont'd.../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312

Fax: 0191 477 9544

e-mail: gblsales@gb lubricants.co.uk

www.gblubricants.co.uk

A division of Goodall Bates & Todd Ltd



CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
SAE	-	-	75W-80
Appearance	-	-	Clear yellow liquid
Density @ 15°C	kg/m ³	ASTM D4052	863
Kinematic Viscosity @ 40°C	cSt	ASTM D445	57.4
Kinematic Viscosity @ 100°C	cSt	ASTM D445	9.6
Viscosity Index	-	ASTM D2270	151
Brookfield viscosity @ -40°C	cP	ASTM D2983	79,980
Pour Point	°C	ASTM D97	-33

STORAGE AND HANDLING

GB GERION® EXTRA 75W-80 should be stored under cover to avoid water collecting in the rim of upturned barrels.

Further information on GB GERION® EXTRA 75W-80 can be obtained by referring to the corresponding Safety Data Sheet.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice.