



TECHNICAL DATA

GB INTERCOOLER 400 15W-40

APPLICATIONS

GB INTERCOOLER 400 15W-40 is a heavy-duty diesel engine oil formulated using the highest quality, virgin Group II mineral base oils and enhanced additive systems for use in both on- and off-highway applications and operating environments such as haulage, plant contracting, mining, agriculture etc.

PERFORMANCE FEATURES

GB INTERCOOLER 400 15W-40 has been developed for use in heavy-duty diesel engines operating both on- and off-highway and offers the following features:

- Excellent anti-wear protection
- Rust and corrosion protection
- Effective control of soot, sludge and piston deposits
- Excellent oxidation and thermal stability
- Extended drain capability

PERFORMANCE DETAILS

GB INTERCOOLER 400 15W-40 may be used where the following specifications are required:

ACEA E7	CUMMINS CES 20077	MERCEDES BENZ 228.3
API CH-4/SJ	DEUTZ DQC-II-10	MTU Type-2
CATERPILLAR ECF-1a	MAN M3275	VOLVO VDS-2

Cont'd.../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312

Fax: 0191 477 9544

e-mail: gblsales@gblubricants.co.uk

www.gblubricants.co.uk

A division of Goodall Bates & Todd Ltd



GB INTERCOOLER 400 15W-40

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
SAE			15W-40
Appearance	-	-	Clear amber liquid
Density @ 15°C	kg/m ³	ASTM D4052	877
Kinematic Viscosity @ 40°C	cSt	ASTM D445	106.3
Kinematic Viscosity @ 100°C	cSt	ASTM D445	14.5
Viscosity Index	-	ASTM D2270	140
CCS -20°C	cP	ASTM D5293	5560

STORAGE AND HANDLING

GB INTERCOOLER 400 15W-40 should be stored under cover to avoid water collecting in the rim of upturned barrels.

Further information on GB INTERCOOLER 400 15W-40 can be obtained by referring to the corresponding Safety Data Sheet.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice.

TDS05.1221.24