



TECHNICAL DATA

GB INTERCOOLER LSC 10W-30

APPLICATIONS

GB INTERCOOLER LSC 10W-30 is a heavy-duty fuel-efficient diesel engine oil, formulated using advanced Group II base oil technology and enhanced additive systems, for use in heavy-duty diesel engines in severe on- and off-highway applications. It may be used in both Euro V and Euro VI engines as well as Tier 4/Stage 4 non-road diesel engines, where a low SAPS product of this quality is specified (sulphated ash, phosphorus and sulphur). Developed to maximise the life of the particulate trap filter, it is backwards compatible and therefore may also be used in older engines.

PERFORMANCE FEATURES

GB INTERCOOLER LSC 10W-30 has been developed for use in heavy-duty diesel engines and offers the following features:


- Low SAPS technology, ensuring protection of the exhaust after-treatment system
- Excellent oxidation and thermal stability
- Excellent anti-wear protection
- Effective control of soot, sludge and piston deposits
- Rust and corrosion protection
- Improved fuel economy
- Extended drain capability

PERFORMANCE DETAILS

The following Original Equipment Manufacturers' formal approvals have been obtained:

VOLVO VDS-4.5	MACK EOS-4.5	RENAULT VI RLD-3
---------------	--------------	------------------

GB INTERCOOLER LSC 10W-30 may also be used where the following specifications are required:

	ACEA E11	DAIMLER TRUCK DTFR 15C100 (MB 228.31)	MAN M3775
	API CK-4	DETROIT DIESEL DFS 93K222	MTU Type 2.1
	CATERPILLAR ECF-3	DEUTZ DQC III-18-LA	
	CUMMINS CES 20086	FORD 171-F1	

Cont'd.../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312
Fax: 0191 477 9544
e-mail: gblsales@gb lubricants.co.uk
www.gb lubricants.co.uk

Trading Name of Goodall Bates & Todd Ltd



CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
SAE			10W-30
Appearance	-	-	Clear amber liquid
Density @ 15°C	kg/m ³	ASTM D4052	875
Kinematic Viscosity @ 40°C	cSt	ASTM D445	76.7
Kinematic Viscosity @ 100°C	cSt	ASTM D445	11.6
Viscosity Index	-	ASTM D2270	144
CCS @ -25°C	cP	ASTM D5293	6516
Flash Point (COC)	°C	ASTM D92	220
Pour Point	°C	ASTM D97	-36
Sulphated Ash	%wt	ASTM D874	1.0

STORAGE AND HANDLING

GB INTERCOOLER LSC 10W-30 should be stored under cover to avoid water collecting in the rim of upturned barrels.

Further information on GB INTERCOOLER LSC 10W-30 can be obtained by referring to the corresponding Safety Data Sheet.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice.