



TECHNICAL DATA

GB INTERCOOLER SUPER 20W-50

APPLICATIONS

GB INTERCOOLER SUPER 20W-50 is a heavy-duty diesel engine oil formulated using the highest quality virgin mineral group II base oils and enhanced additive systems for use in heavy-duty diesel engines in severe on- and off-highway applications in hot climates or high mileage vehicles. Whilst meeting the requirements of both Euro IV and Euro V engines, it is not compatible with Diesel Particulate Trap Filters. This product can also be used in petrol engines fitted in vans and cars where API SL performance is specified.

PERFORMANCE FEATURES

GB INTERCOOLER SUPER 20W-50 offers the following features:

- Excellent anti-wear protection
- Rust and corrosion protection
- Effective control of soot, sludge and piston deposits
- Excellent oxidation and thermal stability
- Extended drain capability



PERFORMANCE DETAILS

GB INTERCOOLER SUPER 20W-50 is formulated to the following quality levels:

| | | |
|---------|-------------|---|
| ACEA E7 | API CI-4/SL | Daimler Truck Fluid Release 15B110 (MB 228.3) |
|---------|-------------|---|

Cont'd.../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312
Fax: 0191 477 9544
e-mail: gblsales@gb lubricants.co.uk
www.gblubricants.co.uk

Trading Name of Goodall Bates & Todd Ltd



GB INTERCOOLER SUPER 20W-50

CHARACTERISTICS

| TEST | UNIT | METHOD | TYPICAL PHYSICAL CHARACTERISTICS |
|-----------------------------|-------------------|------------|----------------------------------|
| SAE | | | 20W-50 |
| Appearance | - | - | Clear amber liquid |
| Density @ 15°C | kg/m ³ | ASTM D4052 | 883 |
| Kinematic Viscosity @ 40°C | cSt | ASTM D445 | 181.9 |
| Kinematic Viscosity @ 100°C | cSt | ASTM D445 | 19.9 |
| Viscosity Index | - | ASTM D2270 | 126 |
| CCS @ -15°C | mPa.s | ASTM D5293 | 8318 |

STORAGE AND HANDLING

GB INTERCOOLER SUPER 20W-50 should be stored under cover to avoid water collecting in the rim of upturned barrels.

Further information on GB INTERCOOLER SUPER 20W-50 can be obtained by referring to the corresponding Safety Data Sheet.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice.

TDS285.0126.12