



# TECHNICAL DATA

## GB TURBO ECO FA 0W-30

### APPLICATIONS

GB TURBO ECO FA 0W-30 is a mid-SAPS engine oil formulated for use in Ford and Jaguar Land Rover's latest technology diesel engines and where superior fuel efficiency performance is required. Can be used in engines specifying low viscosity lubricants, either in gasoline or diesel applications, where the performance levels quoted below are listed. GB TURBO ECO FA 0W-30 has been developed for use in Euro V and VI compliant vehicles with DPF after treatment devices.

### PERFORMANCE FEATURES

GB TURBO ECO FA 0W-30 is recommended for use in the latest Ford and Jaguar Land Rover's engine designs and offers the following features:

- Increased engine efficiency, output and improved fuel economics
- Outstanding cold temperature flow rates and high temperature film strength
- Low levels of volatility
- Superior thermal stability, improved engine cleanliness

### PERFORMANCE DETAILS

GB TURBO ECO FA 0W-30 may be used where the following specifications are required:

ACEA C2	FORD WSS-M2C950-A	STJLR.03.5007
---------	-------------------	---------------

Cont'd.../...

## **GB LUBRICANTS**

Albany Road Gateshead NE8 3BP


Tel: 0191 490 4312

Fax: 0191 477 9544

e-mail: [gblsales@gb lubricants.co.uk](mailto:gblsales@gb lubricants.co.uk)

[www.gblubricants.co.uk](http://www.gblubricants.co.uk)

A division of Goodall Bates & Todd Ltd



# GB LUBRICANTS

**CHARACTERISTICS**

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
<b>SAE</b>			<b>0W-30</b>
Appearance	-	-	Clear amber liquid
Density @ 15°C	kg/m <sup>3</sup>	ASTM D4052	840
Kinematic Viscosity @ 100°C	cSt	ASTM D445	9.5
Kinematic Viscosity @ 40°C	cSt	ASTM D445	45.7
Viscosity Index	-	ASTM D2270	196
Flash Point (PMCC)	°C	ASTM D93	210
Pour Point	°C	ASTM D97	-48

**STORAGE AND HANDLING**

GB TURBO ECO FA 0W-30 should be stored under cover to avoid water collecting in the rim of upturned barrels.

Further information on GB TURBO ECO FA 0W-30 can be obtained by referring to the corresponding Safety Data Sheet.

***The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice.***