



# TECHNICAL DATA

## GB TURBO ECO P 0W-30

### APPLICATIONS

GB TURBO ECO P 0W-30 is a premium synthetic technology, fuel-efficient, passenger car engine oil, formulated using the highest quality virgin base fluids and enhanced additive systems, for use in vehicles with emission control systems. It is suitable for both high performance car and light van diesel and petrol engines in Euro 4, 5 and 6 compliant vehicles, requiring low levels of sulphated ash, phosphorus and sulphur. GB TURBO ECO P 0W-30 has been specially developed for the latest generation of PSA engines, including hybrids and may also be used where the OEM recommends a low viscosity ACEA C2 0W-30 oil, e.g. Honda, Suzuki.

### PERFORMANCE FEATURES

GB TURBO ECO P 0W-30 has been developed for the latest generation of PSA engines requiring a low viscosity oil and offers the following features:

- Mid SAPS technology, ensuring protection of exhaust after-treatment systems
- Improved engine wear protection
- Rust and corrosion protection
- Excellent piston deposit control
- Excellent thermal and oxidation stability
- Improved fuel economy
- Excellent cold-starting and low-temperature performance

### PERFORMANCE DETAILS

GB TURBO ECO P 0W-30 may be used where the following specifications are required:

ACEA C2

PSA B71 2312

Cont'd.../...

## **GB LUBRICANTS**

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312  
Fax: 0191 477 9544  
e-mail: gblsales@gb lubricants.co.uk  
www.gblubricants.co.uk

Trading Name of Goodall Bates & Todd Ltd



**CHARACTERISTICS**

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
<b>SAE</b>	-	-	<b>0W-30</b>
Appearance	-	-	Clear amber liquid
Density	kg/m <sup>3</sup>	ASTM D 4052	844
Kinematic Viscosity @ 100°C	cSt	ASTM D 445	9.9
Kinematic Viscosity @ 40°C	cSt	ASTM D 445	54.9
Viscosity Index	-	ASTM D2270	169
Pour Point	°C	ASTM D 97	-42

**STORAGE AND HANDLING**

GB TURBO ECO P 0W-30 should be stored under cover to avoid water collecting in the rim of upturned barrels.

Further information on GB TURBO ECO P 0W-30 can be obtained by referring to the corresponding Safety Data Sheet.

***The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice.***