



TECHNICAL DATA

GB TURBO SXJ 5W-30

APPLICATIONS

GB TURBO SXJ 5W-30 is a synthetic technology fuel efficient passenger car oil formulated using the highest quality virgin base fluids and enhanced additive systems, for use in both petrol and diesel engines. It has been specifically engineered for use in low emission passenger car engines, where a low SAPS product of this quality is required (sulphated ash, phosphorus and sulphur) and has been developed to maximise the life of the exhaust after-treatment systems. Because of its lower viscosity, it is recognised as a fuel-efficient lubricant which also provides better cold starting and less wear on engines, starter motors and batteries.

PERFORMANCE FEATURES

GB TURBO SXJ 5W-30 has been developed for use in passenger cars fitted with exhaust after-treatment systems and offers the following features:

- Low SAPS technology, ensuring protection of exhaust after-treatment systems
- Improved engine wear protection
- Rust and corrosion protection
- Excellent piston deposit control and engine cleanliness
- Excellent thermal and oxidation stability
- Improved fuel economy

PERFORMANCE DETAILS

GB TURBO SXJ 5W-30 may be used where the following specifications are required:

FORD WSS-M2C934-B

JAGUAR LAND ROVER STJLR.03.5005

Cont'd.../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312
Fax: 0191 477 9544
e-mail: gblsales@gb lubricants.co.uk
www.gblubricants.co.uk

Trading Name of Goodall Bates & Todd Ltd



GB LUBRICANTS

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
SAE			5W-30
Appearance	-	-	Clear amber liquid
Density	kg/m ³	ASTM D4052	844
Kinematic Viscosity @ 100°C	cSt	ASTM D445	10.0
Kinematic Viscosity @ 40°C	cSt	ASTM D445	55.8
Viscosity Index	-	ASTM D2270	168
CCS @ - 30°C	cP	ASTM D5293	4139
Pour Point	°C	ASTM D97	-39
Flash Point	°C	ASTM D93	190

STORAGE AND HANDLING

GB TURBO SXJ 5W-30 should be stored under cover to avoid water collecting in the rim of upturned barrels.

Further information on GB TURBO SXJ 5W-30 can be obtained by referring to the corresponding Safety Data Sheet.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice.