GB TURBO SXL 5W-30

APPLICATIONS

GB TURBO SXL 5W-30 is a premium passenger car oil formulated using the highest quality synthetic technology base fluids and enhanced additive systems for use in both petrol and diesel engines. It has been specifically engineered for VW group cars requiring a mid-SAPS product (sulphated ash, phosphorus and sulphur) meeting VW 504/507 and has been developed to maximise the life of the exhaust after-treatment system. Although originally specifically engineered for VW 504/507, it can be used where all previous VW engine oil specifications are referenced, making it suitable for older engines. It may also be used in vehicles manufactured by other OEMs when the performance and viscosity grade are applicable.

PERFORMANCE FEATURES

GB TURBO SXL 5W-30 has been developed for VW group cars and offers the following features:

- Mid SAPS technology, ensuring protection of exhaust after-treatment systems
- Extended low speed pre-ignition (LSPI) protection
- Improved engine and timing chain wear protection
- Improved sludge and varnish control
- Rust and corrosion protection
- Excellent high temperature deposit protection for pistons and turbo chargers
- Excellent oxidation stability
- Improved fuel economy
- Extended oil drain intervals, compatible with flexible ODI systems

PERFORMANCE DETAILS

GB TURBO SXL 5W-30 may be used where the following specifications are required:

API SQ	MERCEDES BENZ 229.52	OV 040 1547-D30
ACEA C3	PORSCHE C30	OV 040 1547-G30
BMW LL-04	VW 504 00/507 00	

Cont'd.../...

GB LUBRICANTS
Albany Road Gateshead NE8 3BP
Tel: 0191 490 4312
Fax: 0191 477 9544
e-mail: gblsales@gblubricants.co.uk
www.gblubricants.co.uk
Trading Name of Goodall Bates & Todd Ltd

bsi ISO 9001 Quality Management Systems CERTIFIED · ISO 14001 Environmental Management CERTIFIED · ISO 45001 Occupational Health and Safety Management CERTIFIED · ISO 50001 Energy Management CERTIFIED · PAS 99 Integrated Management Systems CERTIFIED

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
SAE			**5W-30**
Appearance	-	-	Clear amber liquid
Density @ 15°C	kg/m^3	IP 160	854
Kinematic Viscosity @ 40°C	cSt	IP 71	71.2
Kinematic Viscosity @ 100°C	cSt	IP 71	11.8
Viscosity Index	-	IP 226	161
CCS @ -30°C	cP	ASTM D5293	6278
Flash Point	°C	IP 34	190
Pour Point	°C	ASTM D97	-42

STORAGE AND HANDLING

GB TURBO SXL 5W-30 should be stored under cover to avoid water collecting in the rim of upturned barrels.

Further information on GB TURBO SXL 5W-30 can be obtained by referring to the corresponding Safety Data Sheet.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice.