



TECHNICAL DATA

GB TURBO SXL 5W-30

APPLICATIONS

GB TURBO SXL 5W-30 is a synthetic passenger car oil formulated using the highest quality synthetic base fluids and enhanced additive systems for use in both petrol and diesel engines. It has been specifically engineered for VW group cars requiring a mid-SAPS product (sulphated ash, phosphorus and sulphur) meeting VW 504/507 and has been developed to maximise the life of the exhaust after-treatment system. Although originally specifically engineered for VW 504/507, it can be used where all previous VW engine oil specifications are referenced, making it suitable for older engines. It may also be used in vehicles manufactured by other OEM's when the performance and viscosity grade are applicable.

PERFORMANCE FEATURES

GB TURBO SXL 5W-30 has been developed for VW group cars and offers the following features:

- Mid SAPS technology, ensuring protection of exhaust after-treatment systems
- Improved engine wear protection
- Improved sludge control and engine cleanliness
- Rust and corrosion protection
- Excellent piston deposit control
- Excellent oxidation stability
- Improved fuel economy
- Extended oil drain intervals, compatible with flexible ODI systems

PERFORMANCE DETAILS

GB TURBO SXL 5W-30 may be used where the following specifications are required:

	API SN	MERCEDES BENZ 229.51
	ACEA C3	PORSCHE C30
	BMW LL-04	VW 504 00/507 00

Cont'd .../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312
Fax: 0191 477 9544
e-mail: gblsales@gblubricants.co.uk
www.gblubricants.co.uk

Trading Name of Goodall Bates & Todd Ltd



CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
SAE			5W-30
Appearance	-	-	Clear amber liquid
Density @ 15°C	kg/m ³	IP 160	852
Kinematic Viscosity @ 40°C	cSt	IP 71	71.2
Kinematic Viscosity @ 100°C	cSt	IP 71	11.8
Viscosity Index	-	IP 226	161
CCS @ -30°C	cP	ASTM D5293	6278
Flash Point	°C	IP 34	190
Pour Point	°C	ASTM D97	-42

STORAGE AND HANDLING

GB TURBO SXL 5W-30 should be stored under cover to avoid water collecting in the rim of upturned barrels.

Further information on GB TURBO SXL 5W-30 can be obtained by referring to the corresponding Safety Data Sheet.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice.