



TECHNICAL DATA

GB TURBO SXV 5W-30

APPLICATIONS

GB TURBO SXV 5W-30 is a synthetic technology passenger car oil formulated using the highest quality virgin base fluids and enhanced additive systems for use in both petrol and diesel engines. It has been specifically engineered for all General Motors cars requiring a product meeting GM Dexos 2 and may also be used where GM-LL-A-025 or GM-LL-B-025 were originally specified. GB TURBO SXV 5W-30 has been developed for use in vehicles with exhaust after-treatment devices including diesel particulate filters (DPF's), and so may also be used in vehicles manufactured by other OEM's when the performance and viscosity grade are applicable.


PERFORMANCE FEATURES

GB TURBO SXV 5W-30 has been developed for high performance cars and offers the following features:

- Mid SAPS technology, ensuring protection of exhaust after-treatment systems
- Improved engine wear protection
- Improved sludge control and engine cleanliness
- Rust and corrosion protection
- Excellent piston deposit control
- Excellent thermal and oxidation stability

PERFORMANCE DETAILS

GB TURBO SXV 5W-30 may be used where the following specifications are required:

	ACEA C3	MERCEDES BENZ 229.51
	API SN/CF	Opel/Vauxhall OV0401547-D30
	GM DEXOS 2	

Cont'd.../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP
Tel: 0191 490 4312
Fax: 0191 477 9544
e-mail: gblsales@gb lubricants.co.uk
www.gblubricants.co.uk

Trading Name of Goodall Bates & Todd Ltd



CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
SAE			5W-30
Appearance	-	-	Clear amber liquid
Density	kg/m ³	ASTM D4052	846
Kinematic Viscosity @ 100°C	cSt	ASTM D445	12.1
Kinematic Viscosity @ 40°C	cSt	ASTM D445	73.6
Viscosity Index	-	ASTM D2270	162
CCS @ -30°C	cP	ASTM D5293	6420
HTHS @ 150°C	mPa.s	ASTM D4683	3.6
Noack	%	ASTM D5800	9
Pour Point	°C	ASTM D97	-36
Flash Point	°C	ASTM D93	204
TBN	mg KOH/g	ASTM D2896	8.1

STORAGE AND HANDLING

GB TURBO SXV 5W-30 should be stored under cover to avoid water collecting in the rim of upturned barrels.

Further information on GB TURBO SXV 5W-30 can be obtained by referring to the corresponding Safety Data Sheet.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice.