



TECHNICAL DATA

GB UNIGREASE® 1754

APPLICATIONS

GB UNIGREASE® 1754 is based on a highly adhesive bitumen incorporating extreme-pressure additives for use in open gears in heavy industry. It is also suitable for the lubrication of large girth gears, heavy wire ropes, chains, flexible couplings, gears and sliding surfaces of drag lines and shovels.

PERFORMANCE FEATURES

GB UNIGREASE® 1754 is formulated for use in industrial applications and offers the following features:

- Adhesive properties
- Load-carrying properties
- Water resistance
- Corrosion protection

METHOD OF APPLICATION

GB UNIGREASE® 1754 can be applied by brush, heated sump or pump. To ensure ease of application it should be stored at a minimum temperature of 15°C

TYPICAL PHYSICAL CHARACTERISTICS

Appearance	-	Black tacky viscous compound
Thickener	-	Bitumen
Base Oil	-	Silicone
Viscosity @ 100°C (ASTM D445)	-	100 cSt
Flash Point (ASTM D93)	-	110°C
Pour Point (ASTM D97)	-	0°C
Operating Temperature Range	-	-15°C to + 80°C

Cont'd.../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312
Fax: 0191 477 9544
e-mail: gblsales@gb lubricants.co.uk
www.gblubricants.co.uk

Trading Name of Goodall Bates & Todd Ltd



GB LUBRICANTS

STORAGE AND HANDLING

GB UNIGREASE® 1754 should be stored under cover to avoid water collecting in the rim of upturned barrels. Ideal storage temperature between 0°C and 25°C, away from moisture and direct sources of heat or sunlight.

Further information on GB UNIGREASE® 1754 can be obtained by referring to the corresponding Safety Data Sheet.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice.