



# TECHNICAL DATA

## **GB UNIGREASE® LEP2**

### **APPLICATIONS**

GB UNIGREASE® LEP2 is a premium quality multi-purpose lithium grease, incorporating extreme-pressure additives for use in all plain and anti-friction bearings subjected to high load conditions.

### **PERFORMANCE FEATURES**

GB UNIGREASE® LEP2 is formulated for use in many applications including agricultural, automotive, construction, commercial, forestry and industrial and offers the following features:

- Mechanical stability
- Oxidation stability
- Load-carrying properties
- Resistance to shock loads
- Anti-wear performance
- Corrosion protection

### **METHOD OF APPLICATION**

GB UNIGREASE® LEP2 can be applied manually, or by using a standard grease gun (400gm & 500gm cartridges available), or via a centralised lubrication system designed for and capable of pumping an NLGI No 2 grease; consult a qualified centralised lubrication systems engineer before installation. As with all greases used for the first time, check compatibility with the grease applied previously and, if necessary, purge bearings prior to application. Likewise, as a general rule, take care not to over-lubricate and only to apply the quantity of grease recommended by the bearing manufacturer.

### **PERFORMANCE DETAILS**

The following Original Equipment Manufacturer's formal approvals have been obtained:

MB-Approval 267.0

DTFR – Approval 33B120

Cont'd.../...

## **GB LUBRICANTS**

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312

Fax: 0191 477 9544

e-mail: [gblsales@gblubricants.co.uk](mailto:gblsales@gblubricants.co.uk)

[www.gblubricants.co.uk](http://www.gblubricants.co.uk)

Trading Name of Goodall Bates & Todd Ltd



# GB LUBRICANTS

**TYPICAL PHYSICAL CHARACTERISTICS**

Appearance	-	Smooth brown grease
NLGI Classification	-	2
Thickener	-	Lithium
Base Oil	-	Mineral oil
Base Oil viscosity @ 40°C (ASTM D445)	-	150 cSt
Dropping point (ASTM D2265)	-	>180°C
Oil Separation, 168 hrs @ 40°C (IP 121)	-	3.7%
Water washout @ 79°C (ASTM D1264)	-	6.2
Copper corrosion (ASTM D4048)	-	1b
Resistance to corrosion Emcor (ASTM D6138)	-	0:0
Corrosion (ASTM D1743)	-	Pass
Four Ball Weld Load (IP 239)	-	280 kgf
Operating Temperature Range	-	-30°C to +140°C

**STORAGE AND HANDLING**

GB UNIGREASE® LEP2 should be stored under cover to avoid water collecting in the rim of upturned pails. Ideal storage temperature between 0°C and 25°C, away from moisture and direct sources of heat or sunlight.

Further information on GB UNIGREASE® LEP2 can be obtained by referring to the corresponding Safety Data Sheet.

***The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice.***