



TECHNICAL DATA

GB UNIQUENCH 32

APPLICATIONS

GB UNIQUENCH 32 is a fast-quench oil that has been developed using the highest quality mineral virgin base oils and specially selected additives for use as a general purpose fast quenching oil.

PERFORMANCE FEATURES

GB UNIQUENCH 32 offers the following features:

- Optimized, accelerated cooling rate
- Oxidation stability
- Minimum sludge and varnish formation
- Non-corrosive
- Excellent GM Quenchometer (ASTM D3520) performance
- Consistent Quenchalyzer (ASTM D6200) performance

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
ISO			32
Appearance	-	-	Clear amber liquid
Density @ 15°C	kg/m ³	ASTM D4052	865
Kinematic Viscosity @ 40°C	cSt	ASTM D445	33.5
Kinematic Viscosity @ 100°C	cSt	ASTM D445	5.7
Viscosity Index	-	ASTM D2270	110
Flash Point, COC	°C	ASTM D92	220

Cont'd.../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312
Fax: 0191 477 9544
e-mail: gblsales@gb lubricants.co.uk
www.gblubricants.co.uk

Trading Name of Goodall Bates & Todd Ltd



STORAGE AND HANDLING

GB UNIQUENCH 32 should be stored under cover to avoid water collecting in the rim of upturned barrels.

Further information on GB UNIQUENCH 32 can be obtained by referring to the corresponding Safety Data Sheet.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice.