



# TECHNICAL DATA

## GB GERION® XTS PLUS 80W-90

### APPLICATIONS

GB GERION® XTS PLUS 80W-90 has been developed using the highest quality virgin mineral base oils and advanced additive systems, for use in light duty and heavy duty axles requiring an API GL-5 level of performance. It may also be used in manual transmissions, when specified by the Original Equipment Manufacturer.

### PERFORMANCE FEATURES

GB GERION® XTS PLUS 80W-90 is formulated with a high level of extreme pressure (EP) additive to provide effective protection and also offers the following features:

- Excellent thermal and oxidation stability
- Superior corrosion protection
- Compatibility with seal elastomers
- Low foaming

### PERFORMANCE DETAILS

GB GERION® XTS PLUS 80W-90 is suitable for use where the following specifications are required:

API GL-5	MIL-L-2105D	SAE J2360
API MT-1	MIL-PRF-2105E	SCANIA STO 1:0
MACK GO-J	MERITOR 076-D	SCANIA STO 1:1G
MAN 342-M1, 342-M2	NATO 0-226	ZF TE-ML 07/08

Cont'd.../...

## **GB LUBRICANTS**

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312

Fax: 0191 477 9544

e-mail: [gblsales@gblubricants.co.uk](mailto:gblsales@gblubricants.co.uk)

[www.gblubricants.co.uk](http://www.gblubricants.co.uk)

A division of Goodall Bates & Todd Ltd



# GB LUBRICANTS

**CHARACTERISTICS**

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
<b>SAE</b>			<b>80W-90</b>
Density @ 15°C	kg/m <sup>3</sup>	ASTM D4052	886
Kinematic Viscosity @ 40°C	cSt	ASTM D445	125.0
Kinematic Viscosity @ 100°C	cSt	ASTM D445	14.0
Viscosity Index	-	ASTM D2270	110
Brookfield Viscosity @ -26°C	cP	ASTM D2983	38,500
Flash Point	°C	ASTM D93	180
Pour Point	°C	ASTM D97	-30

**STORAGE AND HANDLING**

GB GERION® XTS PLUS 80W-90 should be stored under cover to avoid water collecting in the rim of upturned barrels.

Further information on GB GERION® XTS PLUS 80W-90 can be obtained by referring to the corresponding Safety Data Sheet.

***The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice.***