



TECHNICAL DATA

GB UNIGREASE® CZ2

APPLICATIONS

GB UNIGREASE® CZ2 is a premium quality water-resistant grease, for use in industrial and marine applications where excessive levels of water are present, such as water-pumping equipment.

PERFORMANCE FEATURES

GB UNIGREASE® CZ2 is formulated with a special additive to provide additional protection and lubrication where the presence of water or humid conditions can affect performance, and offers the following features:

- High degree of water resistance
- Excellent corrosion protection
- Good sealing properties

METHOD OF APPLICATION

GB UNIGREASE® CZ2 can be applied manually, or via a centralised lubrication systems designed for and capable of pumping an NLGI No 2 grease; consult a qualified centralised lubrication systems engineer before installation. As with all greases used for the first time, check compatibility with the grease applied previously and, if necessary, purge bearings prior to application. Likewise, as a general rule, take care not to over-lubricate and only to apply the quantity of grease recommended by the bearing manufacturer.

TYPICAL PHYSICAL CHARACTERISTICS

Appearance	-	Smooth off-white grease
NLGI Classification	-	2
Thickener	-	Calcium
Base Oil	-	Mineral oil
Base Oil viscosity @ 40°C (ASTM D445)	-	100 cSt
Dropping point (ASTM D2265)	-	140°C min
Copper corrosion (ASTM D4048)	-	1a
Zinc Oxide content	-	5%
Operating Temperature Range	-	-30°C to +110°C

Cont'd.../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312

Fax: 0191 477 9544

e-mail: gblsales@gblubricants.co.uk

www.gblubricants.co.uk

Trading Name of Goodall Bates & Todd Ltd



GB LUBRICANTS

STORAGE AND HANDLING

GB UNIGREASE® CZ2 should be stored under cover to avoid water collecting in the rim of upturned pails. Ideal storage temperature between 0°C and 25°C, away from moisture and direct sources of heat or sunlight.

Further information on GB UNIGREASE® CZ2 can be obtained by referring to the corresponding Safety Data Sheet.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice.