



TECHNICAL DATA

GB GERION® MTFE 75W

APPLICATIONS

GB GERION® MTFE 75W is a premium gear oil, which has been developed using the highest quality synthetic technology base oils and multifunctional additives, for use in automotive gearboxes requiring a low viscosity SAE 75W. This fuel efficient gear oil can be used in manual gearboxes, automated manual gearboxes (AMTs), semi-automatic gearboxes, transaxles and transfer boxes, where a gear oil of this type and viscosity grade is specified.

PERFORMANCE FEATURES

GB GERION® MTFE 75W is formulated as a low viscosity automotive gear oil and offers the following features:

- Fuel saving performance
- Superior cold start fluidity
- Thermal and oxidative stability
- Rust and corrosion protection
- Powerful EP chemistry, protecting gears and syncro elements

PERFORMANCE DETAILS

GB GERION® MTFE 75W is formulated to API GL-4 performance level and has demonstrated no harm in use where the following references are quoted:

Ford WSS M2C-200D2
BMW 2300 7533 818 MTF LT-3, 83 22 0 396 706, 83 22 7 533, 818 MTF LT-3
MTF JWS2271
PSA Standard 9730A8
Toyota 08885-81001, 08885-81081
Volvo 1161839, 1161838
VW/AUDI G 060 726 A2, G 052 171 A2, G 052 512 A2
VW G 070 726 A2
Fiat 9.55550-MZ6
Suzuki 99000-22B27-036

Cont'd.../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312
Fax: 0191 477 9544
e-mail: gblsales@gb lubricants.co.uk
www.gb lubricants.co.uk

Trading Name of Goodall Bates & Todd Ltd



GB LUBRICANTS

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
SAE			75W
Appearance	-	-	Clear amber liquid
Density @ 15°C	kg/m ³	ASTM D4052	842
Kinematic Viscosity @ 40°C	cSt	ASTM D7042	31.9
Kinematic Viscosity @ 100°C	cSt	ASTM D7042	6.43
Viscosity Index	-	ASTM D2270	159
Brookfield Viscosity @ -40°C	cP	ASTM D2983	8540
Pour Point	°C	ASTM D97	-45
Flash Point (PMCC)	°C	ASTM D93	140

STORAGE AND HANDLING

GB GERION® MTFE 75W should be stored under cover to avoid water collecting in the rim of upturned barrels.

Further information on GB GERION® MTFE 75W can be obtained by referring to the corresponding Safety Data Sheet.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice.