



TECHNICAL DATA

GB UNIPRO SAW BLADE OIL 22

APPLICATIONS

GB UNIPRO SAW BLADE OIL 22 is formulated using highly refined, virgin paraffinic base oils. It has been developed for use as a lubricant for band and circular saw blades as part of GB Lubricants' UNIPRO SAW BLADE range of products.

PERFORMANCE FEATURES

GB UNIPRO SAW BLADE OIL 22 offers the following features:

- Excellent lubricity, reduction in friction leading to extended blade life
- Rust and corrosion protection
- Excellent oxidation stability

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
ISO			22
Appearance	-	-	Clear & bright
Density	kg/m ³	ASTM D1298	851
Kinematic Viscosity @ 40°C	cSt	ASTM D445	21.7
Kinematic Viscosity @ 100°C	cSt	ASTM D445	4.4
Viscosity Index	-	ASTM D2270	112
Pour point	°C	ASTM D97	-15
Flash point, COC	°C	ASTM D92	206

STORAGE AND HANDLING

GB UNIPRO SAW BLADE OIL 22 should be stored under cover to avoid water collecting in the rim of upturned barrels.

Further information on GB UNIPRO SAW BLADE OIL 22 can be obtained by referring to the corresponding Safety Data Sheet.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice

GB LUBRICANTS

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312
Fax: 0191 477 9544
e-mail: gblsales@gb lubricants.co.uk
www.gb lubricants.co.uk

A division of Goodall Bates & Todd Ltd

TTDS.UNIPRO22.0522.01



GB LUBRICANTS

