



# TECHNICAL DATA

## GB UNIPRO SAW BLADE OIL X3

### APPLICATIONS

GB UNIPRO SAW BLADE OIL X3 is formulated using specially selected additives and high-quality virgin mineral base oils. It has been developed specifically for use as a lubricant for band and circular saw blades.

### PERFORMANCE FEATURES

GB UNIPRO SAW BLADE OIL X3 offers the following features:

- Excellent lubricity, reduction in friction leading to extended blade life
- Rust and corrosion protection
- Good oxidation stability
- 

### CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
<b>ISO</b>			<b>32</b>
Appearance			Clear & bright
Density @ 15°C	kg/m <sup>3</sup>	IP 160	870
Kinematic Viscosity @ 40°C	cSt	IP 71	32.9
Kinematic Viscosity @ 100°C	cSt	IP 71	5.6
Viscosity Index	-	IP 226	106
Pour point	°C	IP 15	-27
Flash point	°C	IP 34	198

### STORAGE AND HANDLING

GB UNIPRO SAW BLADE OIL X3 should be stored under cover to avoid water collecting in the rim of upturned barrels.

Further information on GB UNIPRO SAW BLADE OIL X3 can be obtained by referring to the corresponding Safety Data Sheet.

***The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice.***

TTDS.UNIPRO.0222

## **GB LUBRICANTS**

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312

Fax: 0191 477 9544

e-mail: [gblsales@gb lubricants.co.uk](mailto:gblsales@gb lubricants.co.uk)

[www.gblubricants.co.uk](http://www.gblubricants.co.uk)

A division of Goodall Bates & Todd Ltd



