



# TECHNICAL DATA

## GB TURBO SX 10W-30

### APPLICATIONS

GB TURBO SX 10W-30 is a premium passenger car engine oil formulated using advanced group II virgin base oils incorporating enhanced additive systems for use in both petrol and diesel engines. These include high-performance, turbo-charged passenger cars as well as older naturally aspirated models; it may also be used in light trucks and vans.

### PERFORMANCE FEATURES

GB TURBO SX 10W-30 has been developed for high performance passenger cars and offers the following features:

- Improved engine wear protection
- Rust and corrosion protection
- Excellent piston deposit control
- Excellent oxidation stability
- Exceptional shear stability

### PERFORMANCE DETAILS

GB TURBO SX 10W-30 may be used where the following specifications are required:

API SN/CF

Cont'd.../...

## **GB LUBRICANTS**

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312  
Fax: 0191 477 9544  
e-mail: gblsales@gb lubricants.co.uk  
www.gblubricants.co.uk

Trading Name of Goodall Bates & Todd Ltd



**CHARACTERISTICS**

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
<b>SAE</b>			<b>10W-30</b>
Appearance	-	-	Clear amber liquid
Density	Kg/m <sup>3</sup>	ASTM D4052	873
Kinematic Viscosity @ 100°C	cSt	ASTM D445	12.0
Kinematic Viscosity @ 40°C	cSt	ASTM D445	84.0
Viscosity Index	-	ASTM D2270	137
CCS @ -25°C	cP	ASTM D5293	6340

**STORAGE AND HANDLING**

GB TURBO SX 10W-30 should be stored under cover to avoid water collecting in the rim of upturned barrels.

Further information on GB TURBO SX 10W-30 can be obtained by referring to the corresponding Safety Data Sheet.

***The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice.***