GB TURBO XPS 5W-30

APPLICATIONS

GB TURBO XPS 5W-30 is a synthetic technology, fuel-efficient engine oil, formulated using the highest quality base fluids and enhanced additive systems, especially developed and tested to comply with Stellantis FPW9.55535/03. This engine oil maximises performance of the latest petrol and diesel engines, including those with exhaust after-treatment devices such as diesel particulate filters (DPF) and SCR AdBlue systems. Also suitable for vehicles using hybrid electric technology.

PERFORMANCE FEATURES

GB TURBO XPS 5W-30 has been developed for high performance car and van petrol and diesel engines, and offers the following features:

- Improved fuel economy, engine efficiency, and output
- Excellent engine wear protection
- Excellent oxidation and thermal stability, improving sludge control and engine cleanliness
- Exhaust after-treatment device compatibility
- Protection against Low-Speed Pre-ignition (LSPI)
- Timing chain and valvetrain wear protection
- Engine cleanliness, including reduced turbocharger deposits
- Outstanding cold-starting performance

PERFORMANCE DETAILS

GB TURBO XPS 5W-30 may be used where the following specifications are required:

ACEA C3	Stellantis FPW9.55535/03	OV 0401547-G30
API SQ	PSA B71 2297	OV 0401547-D30
China GB11121	PSA B71 2290	Stellantis FPW9.55535/05 (outside Europe)

Cont'd…/…

GB LUBRICANTS
Albany Road Gateshead NE8 3BP
Tel: 0191 490 4312
Fax: 0191 477 9544
e-mail: gblsales@gblubricants.co.uk
www.gblubricants.co.uk
Trading Name of Goodall Bates & Todd Ltd

bsi ISO 9001 Quality Management Systems CERTIFIED · ISO 14001 Environmental Management CERTIFIED · ISO 45001 Occupational Health and Safety Management CERTIFIED · ISO 50001 Energy Management CERTIFIED · PAS 99 Integrated Management Systems CERTIFIED

GB TURBO XPS 5W-30

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
SAE	-	-	**5W-30**
Appearance	-	-	Clear amber liquid
Density @ 15°C	kg/m^3	ASTM D4052	852
Kinematic Viscosity @ 100°C	cSt	ASTM D445	12.3
Kinematic Viscosity @ 40°C	cSt	ASTM D445	67.1
Viscosity Index	-	ASTM D2270	184
CCS @ -30°C	mPa.s	ASTM D5293	5900
HTHS @ 150°C	mPa.s	ASTM D4683	3.6
Flash Point (PMCC)	°C	ASTM D93	203
Pour Point	°C	ASTM D97	-42

STORAGE AND HANDLING

GB TURBO XPS 5W-30 should be stored under cover to avoid water collecting in the rim of upturned barrels.

Further information on GB TURBO XPS 5W-30 can be obtained by referring to the corresponding Safety Data Sheet.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations without prior notice.